

Infra-Red

Shrink Tunnel



- *Designed for continuous shrinking of PVC, Polyolefin, & Polypropylene films used in shrink packaging.*
- *Easy to use and reduces labor costs.*
- *Can be used for a variety of products including food, toys, cosmetics, videos, & electronics.*



This shrink tunnel machine is equipped with an adjustable speed conveyor that allows the user to operate the tunnel up to 20 feet per minute. It has two separate temperature controllers for upper and lower heaters. The tunnel is heated on 4 sides by 10 infra-red replaceable tubes. The machine includes a stand and wheels, which allow the user to easily move the machine from one location to another. It can be used on a tabletop or free standing on the floor. The unit runs on 220V and is single phase.

Easy to operate: Turn on the power and the heater. Adjust the conveyor speed according to the thickness of the film. Put the package on the conveyor belt and the film shrinks tightly around the package as it goes through the tunnel.

OPTIONS: Double Conveyor - CN-4520AD
Net Conveyor - CN-4520AN

MODEL	POWER SUPPLY	POWER (WATTS)	TUNNEL DIMENSIONS (L x W x H)
*CN-4015A	1 Ø 220V/240V	6kw	27.6" x 15.7" x 5.9"
CN-4520A	1 Ø 220V/240V	6kw	31.5" x 17.7" x 7.9"
*CN-4530A	1 Ø 220V/240V	6kw	31.5" x 17.7" x 11.8"
*CN-4520AL	1 Ø 220V/240V	8kw	39.4" x 17.7" x 7.9"
*CN-4530AL	1 Ø 220V/240V	8kw	39.4" x 17.7" x 11.8"

**special order stock*

Note: CN-4520A is 220V 6kw
6kw = 6000 Watts (6 x 1000 = 6000 Watts)
6000 Watts divided by 220V = 27.272 Amps

*Last updated 06/24/10
Do not reproduce without permission.*